

MAX PRO

Safety Data Sheet

according to Federal Register Rules and Regulations



MAX PRO CARB CLEANER

Safety Data Sheet

according to Federal Register Rules and Regulations

Revision date: 01/15/2015

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Trade name : Max Pro Carb Cleaner
Product code : CC-004-057

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Carb Cleaner

1.3. Details of the supplier of the safety data sheet

A.V.W. Inc. d.b.a. Max Pro
P.O. BOX 9962
Ft Lauderdale FL
33310 T 954-972-3338

1.4. Emergency telephone number

Emergency number : CHEMTREC 24 Hour 1-800-424-9300

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture Classification (GHS-US)

Compressed gas H280
Muta. 1B H340
Carc. 1B H350
Repr. 2 H361
STOT SE 1 H370
STOT RE 2 H373

Full text of H-phrases: see section 16

Hazard statements (GHS-US) :

H280 - Contains gas under pressure; may explode if heated
H340 - May cause genetic defects
H350 - May cause cancer
H361 - Suspected of damaging fertility or the unborn child
H370 - Causes damage to organs
H373 - May cause damage to organs through prolonged or repeated exposure

Max Pro

Safety Data Sheet

according to Federal Register Rules and Regulations

Precautionary statements (GHS-US) : P201 - Obtain special instructions
P202 - Do not handle until all safety precautions have been read and understood
P210 - Keep away from heat, sparks, open flames, hot surfaces. - No smoking
P211 - Do not spray on an open flame or other ignition source
P251 - Pressurized container: Do not pierce or burn, even after use
P260 - Do not breathe dust, fumes, gas, mist, vapor spray
P264 - Wash affected areas thoroughly after handling
P270 - Do not eat, drink or smoke when using this product
P280 - Wear protective gloves, protective clothing, eye protection, face protection
P307+P311 - If exposed: Call a poison center/doctor
P308+P313 - If exposed or concerned: Get medical advice/attention
P314 - Get medical advice/attention if you feel unwell
P321 - Specific treatment: See section 4.1 on this label
P405 - Store locked up
P410+P403 - Protect from sunlight. Store in a well-ventilated place
P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F
P501 - Dispose of contents/container to appropriate waste disposal facility, in accordance with local, regional, national, international regulations.

2.3. Other hazards

Other hazards not contributing to the : Contains gas under pressure; may explode if heated.

20/08/2014

EN (English US)

1/9

classification

2.4. Unknown acute toxicity (GHS-US)

No data available

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	Classification (GHS-US)
CO2	(CAS No)124-38-9	.3-4%	
Acetone	(CAS No)67-64-1	82%-92%	
n-hexane/Heptane	(CAS No)110-54-3	6%-8%	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361 STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Chronic 2, H411

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. IF exposed or concerned: Get medical advice/attention. Call a POISON CENTER or doctor/physician.

First-aid measures after inhalation : Cough. Remove to fresh air and keep at rest in a position comfortable for breathing.

First-aid measures after skin contact : Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse.

First-aid measures after eye contact : Remove contact lenses, if present and easy to do. Continue rinsing. Rinse cautiously with water for several minutes. Direct contact with the eyes is likely to be irritating. Obtain medical attention if pain, blinking or redness persist.

First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries : Suspected of damaging fertility or the unborn child. May cause genetic defects. May cause cancer. Causes damage to organs. Symptoms/injuries after inhalation : Shortness of breath.

4.3. Indication of any immediate medical attention and special treatment needed

01/15/15

2/9

Max Pro

Safety Data Sheet

according to Federal Register Rules and Regulations

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand. Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Non-Flammable Gas
Explosion hazard : Heat may build pressure, rupturing closed containers and increasing risk of burns and injuries.

5.3. Advice for firefighters

Firefighting instructions : Leaking gas fire: Do not extinguish, unless leak can be stopped safely. Eliminate all ignition sources if safe to do so. Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment. DO NOT fight fire when fire reaches explosives. Evacuate area.
Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.
Other information : Aerosol level 3.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Eliminate every possible source of ignition. No naked lights. No smoking. Isolate from fire, if possible, without unnecessary risk. Remove ignition sources. Use special care to avoid static electric charges.

6.1.1. For non-emergency personnel

Protective equipment : Gloves. Safety glasses.
Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection. Avoid breathing dust, fume, gas, mist, vapor spray.
Emergency procedures : Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment : Dam up the liquid spill.
Methods for cleaning up : Store away from other materials.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Pressurized container: Do not pierce or burn, even after use.
Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. Do not spray on an open flame or other ignition source. Obtain special instructions . Do not handle until all safety precautions have been read and understood. Eliminate all ignition sources if safe to do so. Avoid breathing dust, fume, gas, mist, vapor spray. Do not breathe dust, fumes, gas, mist, vapor spray.
Hygiene measures : Wash affected areas thoroughly after handling.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Proper grounding procedures to avoid static electricity should be followed.
Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Keep container closed when not in use. Do not expose to temperatures exceeding 50 °C/ 122 °F. Keep in fireproof place.
Incompatible products : Strong bases. Strong acids.
Incompatible materials : Sources of ignition. Direct sunlight. Heat sources.
Storage area : Store in a well-ventilated place.

Max Pro

Safety Data Sheet

according to Federal Register Rules and Regulations

7.3. Specific end use(s)

Follow Label Directions.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.2. Exposure controls

Appropriate engineering controls

: Local exhaust ventilation, vent hoods.

Personal protective equipment

: Gloves. Safety glasses. Avoid all unnecessary exposure.



Hand protection

: Wear protective gloves.

Eye protection

: Chemical goggles or safety glasses.

Skin and body protection

: Wear suitable protective clothing.

Respiratory protection

: Where exposure through inhalation may occur from use, respiratory protection equipment is recommended.

Other information

: Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state

: Gas

Appearance

:

Clear, colorless liquid.

Color

: Colorless.

Odor

: characteristic

.

Odor threshold

: none

No data available

pH

:

No data available

Relative evaporation rate (butyl acetate=1)

:

Melting point

: <-20

Freezing point

: No data available

Boiling point

: >38 °C Lowest Component

Flash point

: 0 °

< -18 °C Lowest Component

Auto-ignition temperature

:

No data available

Decomposition temperature

:

No data available

Flammability (solid, gas)

:

No data available

Vapor pressure

:

Relative vapor density at 20 °C

: 1.27 kg/m

Relative density

: 0.69

Solubility

: Insoluble in water.

Max Pro

Safety Data Sheet

according to Federal Register Rules and Regulations

Log Pow	:	No data available
Log Kow	:	No data available
Viscosity, kinematic	:	0.83 cSt
Viscosity, dynamic	:	No data available
Explosive properties	:	No data available
Oxidizing properties	:	No data available
Explosive limits	:	No data available

9.2. Other information

VOC content	:	Within limits
-------------	---	---------------

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

. Contains gas under pressure; may explode if heated. Extreme risk of explosion by shock, friction, fire or other sources of ignition.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Heat. Sparks. Open flame. Overheating.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

Toxic fume. . Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity	:	Not classified
----------------	---	----------------

SECTION 12: Ecological information

12.1. Toxicity

12.2. Persistence and degradability

CLEANER

Persistence and degradability	:	Not established.
-------------------------------	---	------------------

n-hexane (110-54-3)

Persistence and degradability	:	May cause long-term adverse effects in the environment.
-------------------------------	---	---

Acetone(67-64-1)

Persistence and degradability	:	Not established.
-------------------------------	---	------------------

Max Pro

Safety Data Sheet

according to Federal Register Rules and Regulations

12.3. Bioaccumulative potential

CLEANER

Bioaccumulative potential : Not established.

n-hexane (110-54-3)

Bioaccumulative potential : Not established.

Acetone (67-64-1)

Bioaccumulative potential : Not established.

12.4. Mobility in soil

None

12.5. Other adverse effects

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Container under pressure. Do not drill or burn even after use. Dispose of contents/container to appropriate waste disposal facility, in accordance with local, regional, national, international regulations.

Additional information : Flammable vapors may accumulate in the container.

Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

UN1950, Aerosols, 2.1, Limited Quantity
US DOT (ground):
ICAO/IATA (air): UN1950, Aerosols, 2.1, Limited Quantity
IMO/IMDG (water): UN1950, Aerosols, 2.1, Limited Quantity
Special Provisions: N82 - See 173.306 of this subchapter for classification criteria for flammable aerosols.

14.2. UN proper shipping name

DOT Proper Shipping Name : Aerosols
Gas under pressure (each not exceeding 1 L capacity)

Department of Transportation (DOT) Hazard Classes : 2.1 - Class 2.1 – Gas under pressure 49 CFR 173.115

Hazard labels (DOT) : 2.1 – Gas under pressure

DOT Special Provisions (49 CFR 172.102) : N82 - See 173.306 of this subchapter for classification criteria for flammable aerosols.
DOT Packaging Exceptions (49 CFR 173.xxx) : 306

Max Pro

Safety Data Sheet

according to Federal Register Rules and Regulations

DOT Packaging Non Bulk (49 CFR 173.xxx) : None
DOT Packaging Bulk (49 CFR 173.xxx) : None

14.3. Additional information

Other information : No supplementary information available.

Overland transport

No additional information available

Transport by sea

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.

DOT Vessel Stowage Other : 48 - Stow "away from" sources of heat, 87 - Stow "separated from" Class 1 (explosives) except Division 14, 126 - Segregation same as for Class 9, miscellaneous hazardous materials

Air transport

DOT Quantity Limitations Passenger aircraft/rail : 75 kg (49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 150 kg CFR 175.75)

SECTION 15: Regulatory information

15.1. US Federal regulations

CLEANER

SARA Section 311/312 Hazard Classes : Delayed (chronic) health hazard
Fire hazard
Immediate (acute) health hazard

15.2. International regulations

CANADA

CLEANER

WHMIS Classification : Class B Division 5 – Gas under pressure
Class D Division 2 Subdivision B - Toxic material causing other toxic effects

EU-Regulations

No additional information available

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Classification according to Directive 67/548/EEC or 1999/45/EC

Carc.Cat.2; R45
Muta.Cat.2; R46
Repr.Cat.3; R62
F+; R12
Xn; R20/21/22
Xn; R68/20/21/22

Full text of R-phrases: see section 16

Max Pro

Safety Data Sheet

according to Federal Register Rules and Regulations

15.2.2. National regulations

No additional information available

15.3. US State regulations

SECTION 16: Other information

Indication of changes : Revision - See : *

Other information : None.

Full text of phrases: see section 16:	Acute Tox. 3 (Dermal)	Acute toxicity (dermal) Category 3
	Acute Tox. 3 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 3
	Acute Tox. 3 (Oral)	Acute toxicity (oral) Category 3
	Aquatic Chronic 2	Hazardous to the aquatic environment - Chronic Hazard Category 2
	Asp. Tox. 1	Aspiration hazard Category 1
	Carc. 1B	Carcinogenicity Category 1B
	Compressed gas	Gases under pressure Compressed gas
	Flam. Aerosol 1	Flammable aerosol Category 1
	Flam. Liq. 2	Flammable liquids Category 2
	Liquefied gas	Gases under pressure Liquefied gas
	Muta. 1B	Germ cell mutagenicity Category 1B
	Repr. 2	Reproductive toxicity Category 2
	Skin Irrit. 2	Skin corrosion/irritation Category 2
	STOT RE 2	Specific target organ toxicity (repeated exposure) Category 2
	STOT SE 1	Specific target organ toxicity (single exposure) Category 1
	STOT SE 3	Specific target organ toxicity (single exposure) Category 3
	H222	Extremely flammable aerosol
	H225	Highly flammable liquid and vapor
	H280	Contains gas under pressure; may explode if heated
	H301	Toxic if swallowed
	H304	May be fatal if swallowed and enters airways
	H311	Toxic in contact with skin
	H315	Causes skin irritation
	H331	Toxic if inhaled
	H336	May cause drowsiness or dizziness
	H340	May cause genetic defects
	H350	May cause cancer
	H361	Suspected of damaging fertility or the unborn child
	H370	Causes damage to organs
	H373	May cause damage to organs through prolonged or repeated exposure
	H411	Toxic to aquatic life with long lasting effects

NFPA health hazard : 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given.

NFPA fire hazard : 4 - Will rapidly or completely vaporize at normal pressure and temperature, or is readily dispersed in air and will burn readily.

Max Pro

Safety Data Sheet

according to Federal Register Rules and Regulations

NFPA reactivity : 0 - Normally stable, even under fire exposure conditions,
and are not reactive with water.

HMIS III Rating

Health : 2 Moderate Hazard - Temporary or minor injury may occur
Flammability : 1 Severe Hazard
Physical : 1 Slight Hazard
Personal Protection : B

The Supplier identified in Section 1 of this MSDS has evaluated this product and certifies it to be labeled and packaged in compliance with the applicable provisions of the Federal Hazardous Substance Act as stated in 16 CFR 1500 and enforced by the Consumer Product Safety Commission, and where applicable the products that require Child Resistant Closures are packaged in accordance with the Poison Prevention Packaging Act as stated in 16 CFR 1700 and enforced by the Consumer Product Safety Commission. All closures have been tested in accordance with the latest protocols. No other testing is required to certify compliance with the above. The date of manufacture is stamped on the product

Disclaimer: The information and recommendations contained herein are based upon tests believed to be reliable. However, the manufacturer/distributor of this product does not guarantee their accuracy or completeness NOR SHALL ANY OF THIS INFORMATION CONSTITUTE A WARRANTY, WHETHER EXPRESSED OR IMPLIED, AS TO THE SAFETY OF THE GOODS, THE MERCHANTABILITY OF THE GOODS, OR THE FITNESS OF THE GOODS FOR A PARTICULAR PURPOSE. Adjustment to conform to actual conditions of usage may be required. The manufacturer/distributor assumes no responsibility for results obtained or for incidental or consequential damages, including lost profits, arising from the use of these data. No warranty against infringement of any patent, copyright or trademark is made or implied.