

# MAX PRO Electronics Lubricant

## Safety Data Sheet

Federal Register Rules and Regulations

Revision date: 01/15/2015 :

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
Trade name : Electronics Lubricant.  
Product code : LS-004-101, LL-004-125

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : ElectronicsLubricatingSpray

#### 1.3. Details of the supplier of the safety data sheet

A.V.W. Inc d.b.a. Max Pro  
P.O. BOX 9962  
Ft Lauderdale FL 33310  
954-972-3338

#### 1.4. Emergency telephone number

Emergency number : CHEMTREC 24 Hour 1-800-424-9300

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification (GHS-US)

Flam. Aerosol 1 H222  
Compressed gas H280

Full text of H-phrases: see section 16

#### 2.2. Label elements

##### GHS-US labeling

Hazard pictograms (GHS-US)



GHS02



GHS04

Signal word (GHS-US) : Danger

Hazard statements (GHS-US) : H222 - Extremely flammable aerosol  
H280 - Contains gas under pressure; may explode if heated

Precautionary statements (GHS-US) : P210 - Keep away from heat, sparks, open flames, hot surfaces. - No smoking  
P211 - Do not spray on an open flame or other ignition source  
P251 - Pressurized container: Do not pierce or burn, even after use  
P410+P403 - Protect from sunlight. Store in a well-ventilated place  
P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

#### 2.3. Other hazards

Other hazards not contributing to the classification : Contains gas under pressure; may explode if heated.

#### 2.4. Unknown acute toxicity (GHS-US)

No data available

### SECTION 3: Composition/information on ingredients

#### 3.1. Substance

Not applicable

# MAX PRO

## Safety Data Sheet according to Federal Register Rules and Regulations

### 3.2. Mixture

Name	Product identifier	%	Classification (GHS-US)
Aliphatic Petroleum Naptha	(CAS No) 64742-30-9	>= 40-55	Asp. Tox. 1, H304
carbon dioxide, liquefied, under pressure	(CAS No)124-38-9	1 - 5	Compressed gas, H280
Alphatic Hydrocarbon	(CAS No)64742-96-7	>= 40-55	Not classified

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	: Cough. Assure fresh air breathing. Allow the victim to rest.
First-aid measures after skin contact	Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse.
First-aid measures after eye contact	: Direct contact with the eyes is likely to be irritating. Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persist.
First-aid measures after ingestion	: Immediately call a POISON CENTER or doctor/physician. Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation	: Shortness of breath.
Symptoms/injuries after ingestion	: May be fatal if swallowed and enters airways.

### 4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand. Unsuitable extinguishing media : Do not use a heavy water stream.

### 5.2. Special hazards arising from the substance or mixture

Fire hazard	: Extremely flammable aerosol.
Explosion hazard	: Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries.

### 5.3. Advice for firefighters

Firefighting instructions	: Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment. DO NOT fight fire when fire reaches explosives. Evacuate area.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.
Other information	: Aerosol level 3.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : No naked lights. No smoking. Isolate from fire, if possible, without unnecessary risk. Remove ignition sources. Use special care to avoid static electric charges.

#### 6.1.1. For non-emergency personnel

Protective equipment	: Gloves. Safety glasses.
Emergency procedures	: Evacuate unnecessary personnel.

# Max Pro

## Safety Data Sheet Federal Register Rules and Regulations

### 6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.  
Emergency procedures : Ventilate area.

### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

### 6.3. Methods and material for containment and cleaning up

For containment : Dam up the liquid spill.  
Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

### 6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Additional hazards when processed : Hazardous waste due to potential risk of explosion. Pressurized container: Do not pierce or burn, even after use.  
Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. Do not spray on an open flame or other ignition source.  
Hygiene measures : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Proper grounding procedures to avoid static electricity should be followed.  
Storage conditions : Keep only in the original container in a cool, well ventilated place away from: Keep container closed when not in use. Do not expose to temperatures exceeding 50 °C/ 122 °F. Keep in fireproof place.  
Incompatible products : Strong bases. Strong acids.  
Incompatible materials : Sources of ignition. Direct sunlight. Heat sources.  
Storage area : Store in a well-ventilated place.

### 7.3. Specific end use(s)

Follow Label Directions.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### carbon dioxide, liquefied, under pressure (124-38-9)

USA ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	9000 mg/m <sup>3</sup>
USA ACGIH	ACGIH TWA (ppm)	5000 ppm
USA ACGIH	ACGIH STEL (mg/m <sup>3</sup> )	54000
USA ACGIH	ACGIH STEL (ppm)	30000 ppm
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	9000 mg/m <sup>3</sup>
USA OSHA	OSHA PEL (TWA) (ppm)	5000 ppm

### 8.2. Exposure controls

Personal protective equipment : Gloves. Safety glasses. Avoid all unnecessary exposure.



# MAX PRO

## Safety Data Sheet according to Federal Register Rules and Regulations

	:
Hand protection	: Wear protective gloves.
Eye protection	: Chemical goggles or safety glasses.
Respiratory protection	: Wear respiratory protection. Wear appropriate mask.
Other information	: Do not eat, drink or smoke during use.

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Physical state	: Gas
Appearance	:
Color	: Colorless to pale yellow liquid.
Odor	: Colorless. light yellow.
Odor threshold	: characteristic.
pH	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Melting point	: 0.19
Freezing point	: -58 °C
Boiling point	: No data available
Flash point	: > 180 °C
Auto-ignition temperature	: > 84 °C
Decomposition temperature	: 236 °C
Flammability (solid, gas)	: No data available
Vapor pressure	: No data available
Relative vapor density at 20 °C	: 0.013 kPa
Relative density	: 4.5
Solubility	: 0.8
Log Pow	: Insoluble in water.
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: 1.92 cSt @40c
	: No data available

# Max Pro

## Safety Data Sheet Federal Register Rules and Regulations

Explosive properties :  
:  
No data available

Oxidizing properties : No data available

Explosive limits No data available

### 9.2. Other information

Within VOC Limits :

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No additional information available

### 10.2. Chemical stability

Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Extreme risk of explosion by shock, friction, fire or other sources of ignition.

### 10.3. Possibility of hazardous reactions

Not established.

### 10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Heat. Sparks. Open flame. Overheating.

### 10.5. Incompatible materials

Strong acids. Strong bases.

### 10.6. Hazardous decomposition products

Toxic fume. . Carbon monoxide. Carbon dioxide.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity

: Not classified

#### Aliphatic Hydrocarbon (64742-96-7)

LD50 oral rat > 19200 mg/kg (Rat)  
: Not classified

Skin corrosion/irritation : Not classified  
Serious eye damage/irritation : Not classified  
Respiratory or skin sensitization : Not classified  
Germ cell mutagenicity : Not classifiedBased on available data, the classification criteria are not met  
Carcinogenicity : Not classified  
: Not classifiedBased on available data, the classification criteria are not met

Reproductive toxicity : Not classified  
Specific target organ toxicity (single exposure) : Not classified  
: Not classifiedBased on available data, the classification criteria are not met

Specific target organ toxicity (repeated exposure)

# MAX PRO

## Safety Data Sheet according to Federal Register Rules and Regulations

:  
: Not classified Based on available data, the classification criteria are not met

Aspiration hazard

Potential Adverse human health effects and symptoms

: Based on available data, the classification criteria are not met.

Symptoms/injuries after inhalation

: Shortness of breath.

Symptoms/injuries after ingestion

: May be fatal if swallowed and enters airways.

### SECTION 12: Ecological information

#### 12.1. Toxicity

##### carbon dioxide, liquefied, under pressure (124-38-9)

LC50 fish 1	35 mg/l (96 h; Salmogairdneri (Oncorhynchusmykiss); Lethal)
LC50 fish 2	60 - 240 mg/l (12 h; Salmogairdneri (Oncorhynchusmykiss); Lethal)

#### 12.2. Persistence and degradability

##### Lubricant

Persistence and degradability Not established.

##### Aliphatic Hydrocarbon (64742-96-7)

Persistence and degradability Readily biodegradable in water. Biodegradable in the soil. Adsorbs into the soil. Photodegradation in the air.

# Max Pro

## Safety Data Sheet according to Federal Register Rules and Regulations

### Aliphatic Hydrocarbon (64742-96-7)

Chemical oxygen demand (COD)	2.25 g O <sub>2</sub> /g substance
ThOD	2.89 g O <sub>2</sub> /g substance
BOD (% of ThOD)	> % ThOD (5 day(s)) > 0.5

### carbon dioxide, liquefied, under pressure (124-38-9)

Persistence and degradability	Biodegradability: not applicable. No (test) data on mobility of the substance available.
Biochemical oxygen demand (BOD)	Not applicable
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
BOD (% of ThOD)	Not applicable

### 12.3. Bioaccumulative potential

#### Lubricant

Bioaccumulative potential	Not established.
---------------------------	------------------

### Aliphatic Hydrocarbon (64742-96-7)

Log Pow	5.24 - 7.18 (QSAR)
Bioaccumulative potential	Not established.

### carbon dioxide, liquefied, under pressure (124-38-9)

Log Pow	0.83 (Experimental value)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

### 12.4. Mobility in soil

### Aliphatic Hydrocarbon (64742-96-7)

Surface tension	0.033 N/m (20 °C)
-----------------	-------------------

### 12.5. Other adverse effects

Other information	: Avoid release to the environment.
-------------------	-------------------------------------

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Waste disposal recommendations	: Dispose of contents/container to appropriate waste disposal facility, in accordance with local, regional, national, international regulations. . Dispose in a safe manner in accordance with local/national regulations. Container under pressure. Do not drill or burn even after use.
Additional information	: Flammable vapors may accumulate in the container.
Ecology - waste materials	: Hazardous waste due to toxicity. Avoid release to the environment.

## SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

	UN1950, Aerosols, 2.1, Limited Quantity
US DOT (ground):	
ICAO/IATA (air):	UN1950, Aerosols, 2.1, Limited Quantity

# MAX PRO

## Safety Data Sheet according to Federal Register Rules and Regulations

IMO/IMDG (water): UN1950, Aerosols, 2.1, Limited Quantity  
Special Provisions: N82 - See 173.306 of this subchapter for classification criteria for flammable aerosols.

### 14.2. UN proper shipping name

DOT Proper Shipping Name : Aerosols flammable, (each not exceeding 1 L capacity)  
Department of Transportation (DOT) Hazard Classes : 2.1 - Class 2.1 - Flammable gas 49 CFR 173.115  
Hazard labels (DOT) : 2.1 - Flammable gas



DOT Special Provisions (49 CFR 172.102) : N82 - See 173.306 of this subchapter for classification criteria for flammable aerosols.  
DOT Packaging Exceptions (49 CFR 173.xxx) : 306  
DOT Packaging Non Bulk (49 CFR 173.xxx) : None  
DOT Packaging Bulk (49 CFR 173.xxx) : None

### 14.3. Additional information

Other information : No supplementary information available.

#### Overland transport

No additional information available

#### Transport by sea

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.  
DOT Vessel Stowage Other : 48 - Stow "away from" sources of heat, 87 - Stow "separated from" Class 1 (explosives) except Division 14, 126 - Segregation same as for Class 9, miscellaneous hazardous materials

#### Air transport

DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 75 kg  
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 150 kg

## SECTION 15: Regulatory information

### 15.1. US Federal regulations

#### Lubricant

SARA Section 311/312 Hazard Classes : Delayed (chronic) health hazard  
Immediate (acute) health hazard  
Fire hazard  
Sudden release of pressure hazard

### 15.2. International regulations

#### CANADA

#### Lubricant

WHMIS Classification : Class B Division 5 - Flammable Aerosol

#### EU-Regulations



# Max Pro

## Safety Data Sheet according to Federal Register Rules and Regulations

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Classification according to Directive 67/548/EEC or 1999/45/EC Not classified

### 15.2.2. National regulations

### 15.3. US State regulations

No additional information available

## SECTION 16: Other information

Indication of changes : Revision - See : \*

Other information : None.

Full text of H-phrases: see section 16:

Asp. Tox. 1

Compressed gas

Flam. Aerosol 1

H222

H280

H304

Aspiration hazard Category 1

Gases under pressure Compressed gas

Flammable aerosol Category 1

Extremely flammable aerosol


Contains gas under pressure; may explode if heated

May be fatal if swallowed and enters airways

NFPA health hazard : 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given.

NFPA fire hazard : 3 - Liquids and solids that can be ignited under almost all ambient conditions.

NFPA reactivity : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



### HMIS III Rating

Health : 2 Moderate Hazard - Temporary or minor injury may occur

Flammability : 3 Serious Hazard

Physical : 1 Slight Hazard

Personal Protection : B

*The Supplier identified in Section 1 of this MSDS has evaluated this product and certifies it to be labeled and packaged in compliance with the applicable provisions of the Federal Hazardous Substance Act as stated in 16 CFR 1500 and enforced by the Consumer Product Safety Commission, and where applicable the products that require Child Resistant Closures are packaged in accordance with the Poison Prevention Packaging Act as stated in 16 CFR 1700 and enforced by the Consumer Product Safety Commission. All closures have been tested in accordance with the latest protocols. No other testing is required to certify compliance with the above. The date of manufacture is stamped on the product*

*Disclaimer: The information and recommendations contained herein are based upon tests believed to be reliable. However, the manufacturer/distributor of this product does not guarantee their accuracy or completeness NOR SHALL ANY OF THIS INFORMATION CONSTITUTE A WARRANTY, WHETHER EXPRESSED OR IMPLIED, AS TO THE SAFETY OF THE GOODS, THE MERCHANTABILITY OF THE GOODS, OR THE FITNESS OF THE GOODS FOR A PARTICULAR PURPOSE. Adjustment to conform to actual conditions of usage may be required. The*

# MAX PRO

## Safety Data Sheet according to Federal Register Rules and Regulations

---

*manufacturer/distributor assumes no responsibility for results obtained or for incidental or consequential damages, including lost profits, arising from the use of these data. No warranty against infringement of any patent, copyright or trademark is made or implied.*